



[U Type
Flashtubes](#)

[Helical & Toroidal Types
Flashtubes](#)

[Flash Tube/ Trigger Coil
Combination](#)

[Flashtubes General
Information](#)

CATALOG NUMBER	SHAPE / FIG	ANODE TO CATHODE VOLTAGE (V)		MAX ENERGY PER FLASH (WS)	FLASHES WITH MAX ENERGY INPUT		TRIGGER		DIMENSIONS(mm)				APPLICATIONS
		MIN	NOM		MAX FLASH RATE (MIN)	NOMINAL LIFE (NO.OF FLASHES)	MIN VO (KV)	MIN INPUT (MWS)	e	l	d	A	
L-3222	1	200	330	15	6	3,000	4	0.6	10	22	3.2	26	Photographic
L-3228	1	200	330	20	6	3,000	4	0.6	15	28	3.2	32	Photographic
L-3235	1	200	360	25	6	3,000	4	0.6	20	35	3.2	39	Photographic
L-3245	1	220	360	45	6	3,000	4	0.6	30	45	3.2	49	Photographic
L-37285	1	200	360	20	6	3,000	4	0.6	15	28.5	3.7	34	Photographic
L-3735	1	220	360	25	6	3,000	4	0.6	20	35	3.7	39	Photographic
L-3740	1	220	360	35	6	3,000	4	0.6	25	40	3.7	44	Photographic
L-3745	1	220	360	45	6	3,000	4	0.6	30	45	3.7	49	Photographic
L-4040	1	220	360	40	6	3,000	4	0.6	25	40	4	44	Photographic
L-4045	1	220	360	50	6	3,000	4	0.6	30	45	4	49	Photographic
L-4050	1	220	360	60	6	3,000	4	0.6	35	50	4	54	Photographic
L-4055	1	250	360	70	6	3,000	6	0.9	40	55	4	60	Photographic
L-6060	1	250	360	80	6	3,000	6	0.9	40	60	6	66	Photographic
L-6070	1	250	360	90	6	3,000	6	0.9	45	70	6	76	Photographic
L-6032	2	200	300	0.1	6,000	1x10 ⁶	4	0.6	10	29.5±1	6	32±1.5	Timing Light
L-6033	3	200	300	0.1	6,000	1x10 ⁶	4	0.6	10	29.5±1.5	6	32±1.5	Timing Light
L-6038	3	200	300	0.1	6,000	1x10 ⁶	4	0.6	18	38±1.5	6	41.5±1.5	Timing Light
L-3728s	1	180	350	0.5	60	1x10 ⁶	4	0.6	15	28	3.7	32	Timing Light & Signal
L-3730s	1	180	350	0.5	60	1x10 ⁶	4	0.6	15	30	3.7	34	Timing Light & Signal
L-3735s	1	180	350	0.8	60	1x10 ⁶	4	0.6	20	35	3.7	39	Timing Light & Signal
L-4030s	1	180	350	0.5	60	1x10 ⁶	4	0.6	15	30	4	34	Timing Light & Signal
L-4040s	1	200	350	1	60	1x10 ⁶	4	0.6	25	40	4	44	Timing Light & Signal