



[Linear Flashtubes](#)

[Helical & Toroidal Flashtubes](#)

[Flash Tube/ Trigger Coil Combination](#)

[Flashtubes General Information](#)

CATALOG NUMBER	SHAPE /FIG	ANODE TO CATHODE VOLTAGE(V)			MAX ENERGY PER FLASH (WS)	FLASHES WITH MAX ENERGY INPUT		TRIGGER		DIMENSIONS (mm)				APPLICATIONS	
		MIN	MON	MAX		FLASH RATE (MIN)	NOMINAL LIFE (NO. OF FLASHES)	MIN VO (KV)	MIN INPUT (MWS)	l	d	a	c		
U-1221 (Non-Polarized)	4	200	300	400	4	60	1x10 ⁶	4	0.6	29	6	19	40	Signal & Timing Light	
U-4425	5	200	300	400	4	60	1x10 ⁶	4	0.6	32	6	10	40	Signal & Timing Light	
U-6531	5	250	300	400	60	6	1x10 ⁴	6	0.8	38	6	13.5	40	Photographic	
U-8538	5	300	400	600	100	6	1x10 ⁴	6	0.8	45	8	17	40	Photographic	
U-104A	6	200	300	400	0.4	6,000	1x10 ⁶	4	0.6	32	6	10	15	Signal & Timing Light	
U-106	6	200	300	400	60	6	1x10 ⁴	6	0.8	32	6	16	16	Photographic	
U-106A	6	180	315	400	0.4	6,000	1x10 ⁶	4	0.6	32	6	16	15	Signal & Timing Light	
U-106AB	7	180	315	400	0.4	6,000	1x10 ⁶	4	0.6	32	6	10	15	Signal & Timing Light	
U-507	5	250	300	400	50	6	1x10 ⁴	6	0.8	32	6	10	40	Photographic	
U-110	6	250	400	500	100	6	1x10 ⁴	6	0.8	50	6	16	15	Photographic	
U-112 (Non Polarized)	8	350	450	600	350	6	1x10 ⁴	6	0.9	80	d1 6	d2 10	17	75	Photographic
U-0661 (Non Polarized)	9	270	350	500	8	60	2x10 ⁶	4	0.6	40	6	13.5	40	Signal & Warning becons	
U-4668 (Non Polarized)	5	250	400	500	45	20	2x10 ⁶	6	0.8	40	6	16	40	Signal & Warning becons	
U-114 (Non Polarized)	5	200	300	400	4	60	1x10 ⁶	4	0.6	32	6	10	40	Signal & Warning becons	